Mighty Marker® High Purity Marker MM-09







Specifications







Black Ink	White Paint	Yellow Paint	Red Paint
(XV-12149)	(XV-790)	(XV-791)	(XV-830)
00109	01309	01409	01109

Stroke
1.2mm Chisel Fine Edge
4.2mm Chisel Medium Edge 7.2mm Chisel Broad Edge 3.2mm Bullet Tip***

Replacement Nibs #09000 Acrylic or M-Felt Chisel Nib #02200 M-felt Bullet Nib ***Bullet available for Black only.

Barrel

Aluminum

Indicates color of paint

Paint/Ink Content 17ml

Packed Quantities

72 per carton

Temperature Range

For black, use at: -20°F to 130°F (-29°C to 130°C) For all other colors, use at: -40°F to 150°F (-40°C to 66°C)

Solvent System

For Black: Dye Based "Alcohol"

All other colors: Pigmented Paints "Aromatic Solvent"


Dry Time

30 seconds or less

<u>Inks and paints meet or exceed the requirements of:</u> GE# D50TF8-S7 "Nuclear Grade"

Nuclear Plant # TEC 10000028213 Pratt & Whitney # PWA 36700 Rolls Royce # EMA 56752 Chicago Bridge & Iron Westinghouse APP-GW-Z0-602 Various other aerospace and nuclear grade specifications

Directions for Use



- ®
- SHAKE WELL before use, keeping cap in place. (only necessary with paint colors)
- To start, press fiber tip down for several seconds. Repeat until tip is saturated.
- To re-ink, press down once.



158 West Forest Avenue, Englewood NJ 07631 **Toll Free**: 1-888-440-ARRO(2776) **Phone:** (201) 567-4112 | **Fax:** (201) 567-1373 Website: www.arromark.com | Email: sales@arromark.com