

Mighty Marker® High Purity Fine Line Marker MM-06



Specifications



Black Ink (XV-12149)	White Paint (XV-790)	Yellow Paint (XV-791)	Red Paint (XV-830)
00106	01306	01406	01106

Stroke

Imm Extra Fine Bullet Tip

Replacement Nibs

(Polyester or Acrylic) #00085
Extra-Fine Bullet Nib

Barrel

Aluminum

Cap

Indicates color of paint

Paint Content

3ml

Inks and paints meet or exceed the requirements of:

GE# D50TF8-S7 "Nuclear Grade"
Nuclear Plant # TEC 10000028213
Pratt & Whitney # PWA 36700
Rolls Royce # EMA 56752
Chicago Bridge & Iron
Westinghouse APP-GW-Z0-602
Various other aerospace and nuclear grade specifications

Packed Quantities

12 per box
144 per carton
576 per master carton

Dimensions of Carton

12.0" x 7.8" x 4" (L x W x H)

Weight of Master Carton

36 lbs

Temperature Range

Use at -50°F to 150°F
(-46°C to 66°C)

Solvent System

For Black: Dye Based "Alcohol"

All other colors: Pigmented Paints
"Aromatic Solvent"


Dry Time

30 seconds or less

Marker Dimensions with Cap Closed

5.625" L x 0.3125" W
(142.875 x 8.255 mm.)

Directions for Use



- SHAKE WELL before use, keeping cap in place. (only necessary with paint colors)
- To start, press fiber tip down for several seconds. Repeat until tip is saturated.
- To re-ink, press down once.



Arro-Mark®
COMPANY, L.L.C.

158 West Forest Avenue, Englewood NJ 07631
Toll Free: 1-888-440-ARRO(2776)
Phone: (201) 567-4112 | Fax: (201) 567-1373
Website: www.arromark.com | Email: sales@arromark.com